

Insulation Resistance Tester

(Battery Operated)



The complete toolbox for testing and analyzing insulation quality of electrical equipment

Features

- Up to 10KV and 10TΩ
- Measuring insulation resistance from 500KΩ to 10TΩ
- Adjustable Output Voltage from 250VDC to 10KVDC
- Battery and main line operated with fast charge
- Over 16 hours battery operation time
- Impact, water and dust resistant
- Portable, heavy-duty, and light weight case
- Extremely reliable and easy to use
- USB, WIFI connectivity
- User-friendly mobile app.

Application

- High power transformer manufacturers
- Circuit breaker manufacturers
- Repair and maintenance of electrical power plant companies
- Electrical power plant EPC companies
- Electrical power labs
- Big factories e.g. Steel, petrochemicals, refineries, and...
- Household electrical appliances manufacturers



IRT10 Specifications

Specifications are valid at nominal input voltage and an ambient temperature of +25°C, (77°F). Specifications are subject to change without notice.

Gene	
Туре	Portable Insulation Resistance Tester
Main Voltage	100-240V AC/DC , 50 Hz
Built-in Battery With Automatic Charger	Li-ion, 11.1V/ 7800 mAh
Charge Time	2 Hours Full Charge
Battery Run Time	16 Hours 5KV @ 1GΩ Load
Dimensions (L x W x H)	Basic Unit 310 x 270 x 145 mm
Weight	4.5 kg
CAT Rating	CATIV 600V
Opera	
Test Types	IR(t), DAR, PI, (SV, Ramp Test (optional))
Resistance Measurement Range	500 KΩ to 10 TΩ
Resistance Measurement Accuracy	$\pm 5\%$ up to 100 G Ω \pm 20% up to 10 T Ω
Current Range And Measurement Accuracy	1 nA to 1.4 mA ± 5% ± 0.5 nA @ 50 nA
Voltage Measurement Accuracy	±1% reading ± 10V
Output Voltage	500, 1000, 2500, 5000, 10000 VDC
	Adjustable from 250 VDC to 10 KVDC
Enviro	nment
Operating Temperature	-20 to 55 °C (-4 to 131 °F)
Storage Temperature	-30 to 70 °C (-22 to 158 °F)
Humidity	20% – 95% RH , Non-Condensing
Measurement Interval Miscella	
HV LED Ir	ndicator
Storage Capacity Fo	or Over 430 Tests
Internal There	
USB, WIFI C	onnectivity
User-friendly N	
PC Soft	17.3
Access	
	Power & USB Cables
3 x 3m High Voltage Probe Cables With Clamps (Black, Red, Blue)	
3 x 311 High Voltage Frobe Cables With Clamps (Dlack, Ned, Dide)	
	Case Cover

One Year Warranty, Five Years After Sales Services

Tarbiat Modares Science&Technology Park, Pajouhesh Bld, 17th km of Tehran-Karaj Highway Tehran-Iran **TAPCO:**

Tel:+98 21 44180002

Fax:+98 21 44184989